


## Roulement conique 358-354X-TIMKEN - 358-354X-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/358-354x-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>1)</sup> C <sub>1</sub>	Static <sup>2)</sup> C <sub>0</sub>	Dynamic <sup>3)</sup> C <sub>10</sub>	Static <sup>4)</sup> C <sub>0</sub>	Factor <sup>5)</sup> K	Inner	Outer	
mm	mm	mm	N	N	N	N				
45.000	85.000	20.638	9700	13500	25100	34200	1.51	358	354X	
1.7717	3.3465	0.8125	2380	3350	6450	8700				

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>		
Width B	Width C	ER. Dr. α <sup>6)</sup>	Max Shaft Fillet Radius R <sup>7)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sup>8)</sup>	Backing Shoulder Dia. D <sub>1</sub>	Cage A <sub>1</sub> <sup>9)</sup>	A <sub>2</sub> <sup>10)</sup>						
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
21.682	17.462	-4.8	1.5	58.8	53.8	1.5	80.0	73.8	8.4	1.7	30.0	12.2	0.0732	8.58
0.8540	0.6875	-0.19	0.06	1.97	2.09	0.06	3.15	2.02	0.07	0.07				1.12

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952314655
Diam. intérieur	45 mm
Diam. extérieur	85 mm
Épaisseur	20.638 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE