


Roulement conique

L305648-L305610-TIMKEN - L305648-L305610-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/l305648-l305610-timken>

TAPERED ROLLER BEARINGS
SINGLE ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Factor ⁽³⁾ f	Dynamic ⁽¹⁾ C ₀₂	Factor ⁽³⁾ K	Static C ₀	Inner	Outer	
mm	mm	mm	N			N		N			
49.987	80.962	18.258	42000	2.30	1.65	13000	9500	1.64	89000	L305648	L305610
1.5880	3.1875	0.7188	13700			3640	2760		23000		

Bearing Dimensions										Geometry Factors			Bearing Weight																																												
Shaft					Housing					Cage	G ₁	G ₂		C ₃																																											
Width B	Width C	ER. Dr. a ⁽¹⁾	Max. Shaft Fillet Radius R ₁	Backing Shoulder Dia. d ₁	Max. Housing Fillet Radius r ⁽¹⁾	Backing Shoulder Dia. D ₁	Backing Shoulder Dia. D ₂	A ₁ ⁽¹⁾	A ₂ ⁽¹⁾				A ₃ ⁽¹⁾		A ₄ ⁽¹⁾	A ₅ ⁽¹⁾	A ₆ ⁽¹⁾	A ₇ ⁽¹⁾	A ₈ ⁽¹⁾	A ₉ ⁽¹⁾	A ₁₀ ⁽¹⁾	A ₁₁ ⁽¹⁾	A ₁₂ ⁽¹⁾	A ₁₃ ⁽¹⁾	A ₁₄ ⁽¹⁾	A ₁₅ ⁽¹⁾	A ₁₆ ⁽¹⁾	A ₁₇ ⁽¹⁾	A ₁₈ ⁽¹⁾	A ₁₉ ⁽¹⁾	A ₂₀ ⁽¹⁾	A ₂₁ ⁽¹⁾	A ₂₂ ⁽¹⁾	A ₂₃ ⁽¹⁾	A ₂₄ ⁽¹⁾	A ₂₅ ⁽¹⁾	A ₂₆ ⁽¹⁾	A ₂₇ ⁽¹⁾	A ₂₈ ⁽¹⁾	A ₂₉ ⁽¹⁾	A ₃₀ ⁽¹⁾	A ₃₁ ⁽¹⁾	A ₃₂ ⁽¹⁾	A ₃₃ ⁽¹⁾	A ₃₄ ⁽¹⁾	A ₃₅ ⁽¹⁾	A ₃₆ ⁽¹⁾	A ₃₇ ⁽¹⁾	A ₃₈ ⁽¹⁾	A ₃₉ ⁽¹⁾	A ₄₀ ⁽¹⁾	A ₄₁ ⁽¹⁾	A ₄₂ ⁽¹⁾	A ₄₃ ⁽¹⁾	A ₄₄ ⁽¹⁾	A ₄₅ ⁽¹⁾	A ₄₆ ⁽¹⁾
18.258	14.286	-2.5	1.5	55.8	57.8	1.5	77.0	79.0	8.2	2.8	35.9	20.8	0.0841	0.36	0.79																																										
0.7188	0.5625	-0.10	0.06	2.17	2.24	0.06	3.03	3.07	0.01	0.08																																															

CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952315577
Diam. intérieur	49.987 mm
Diam. extérieur	80.962 mm
Épaisseur	18.258 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE