

## Roulement conique 6465-6420A-TIMKEN - 6465-6420A-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/6465-6420a-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> K	Dynamic <sup>(3)</sup> C <sub>02</sub>	Factor <sup>(4)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
57.150	149.225	53.975	41100	2.30	10700	6800	1.61	40300	6465	6420A
2.250	5.8750	2.1250	5260		2400	1480		10400		

  

Bearing Dimensions										Geometry Factors			Bearing Weight
Shaft					Housing					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>	
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sup>(2)</sup>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>(3)</sup>	A <sub>2</sub> <sup>(4)</sup>	A <sub>3</sub> <sup>(5)</sup>				kg
54.225	44.400	-15.8	0.8	75.0	0.8	140.0	131.0	2.7	0.7	158.3	20.1	0.0021	5.89
2.1250	1.7500	-0.58	0.27	2.95	0.03	5.51	5.18	0.10	0.03				11.22

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952318233
Diam. intérieur	57.15 mm
Diam. intérieur	2 1/4" inch
Diam. extérieur	149.225 mm
Diam. extérieur	5 7/8" inch
Epaisseur	53.975 mm
Epaisseur	2 1/8" inch
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE