

Roulement conique 3982X-3927AS-TIMKEN - 3982X-3927AS-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/3982x-3927as-timken>

TAPERED ROLLER BEARINGS
SINGLE ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | | |
|--------------------|---------|---------|--------------------------------------|-------------------------------------|------------------------|---------------------------------------|--------------------------------------|------------------------|-------------------------------------|-------|--------|
| Bore d | O.D. D | Width T | Dynamic ¹⁾ C ₁ | Static ²⁾ C ₀ | Factor ³⁾ K | Dynamic ⁴⁾ C ₉₀ | Static ⁵⁾ C ₁₀ | Factor ⁶⁾ K | Static ⁷⁾ C ₀ | Inner | Outer |
| mm | mm | mm | N | N | | N | N | | N | | |
| 63.500 | 110.000 | 29.370 | 139000 | 212000 | 1.45 | 30000 | 24800 | 1.45 | 191000 | 3982X | 3927AS |
| 2.5000 | 4.3307 | 1.1563 | | | | 8000 | 5510 | | 43000 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|-------------------------|--|--------------------------------------|--|--------------------------------------|-----------------------------------|------------------------------|----------------|------------------|----------------|------|----------------|------|
| Shaft | | | | | Housing | | | | | Cage | | | | |
| Width B | Width C | ER. Dr. α ¹⁾ | Max. Shaft Fillet Radius R ²⁾ | Backing Shoulder Dia. d _s | Max. Housing Fillet Radius r ³⁾ | Backing Shoulder Dia. D _s | Cage A ₁ ⁴⁾ | A ₂ ⁵⁾ | G ₁ | G ₂ | C ₃ | kg | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | mm | | |
| 30.048 | 23.020 | -4.6 | 7.0 | 71.0 | 84.0 | 0.5 | 105.0 | 101.0 | 2.2 | 1.2 | 75.2 | 21.3 | 0.1002 | 1.10 |
| 1.1920 | 0.9092 | -0.18 | 0.28 | 2.80 | 3.31 | 0.02 | 4.13 | 3.94 | 0.08 | 0.05 | | | | 2.43 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952319124 |
| Diam. intérieur | 63.5 mm |
| Diam. extérieur | 110 mm |
| Épaisseur | 29.37 mm |
| Conditionnement | 1 |
| Norme | Sans norme |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE