

## Roulement conique 656-652A-TIMKEN - 656-652A-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/656-652a-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(3)</sup> C <sub>02</sub>	Factor <sup>(4)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
64.960	149.225	41.275	247000	2.41	64000	46800	1.43	270000	008	052A
2.5575	5.8750	1.6250	55500		14400	10700		75300		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft		Housing		Cage					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>			
Width B	Width C	ER. Dr. a <sup>(1)</sup>	Max. Shaft Fillet Radius R <sup>(2)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sup>(3)</sup>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>(4)</sup>	A <sub>2</sub> <sup>(5)</sup>						
41.275	31.750	-3.8	3.5	78.6	85.8	3.3	141.8	132.8	4.5	2.1	136.6	27.3	0.0918	3.88
1.6250	1.2500	-0.31	0.14	3.07	3.35	0.13	5.55	5.20	0.17	0.08				7.89

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952319544
Diam. intérieur	64.96 mm
Diam. intérieur	2.557" inch
Diam. extérieur	149.225 mm
Diam. extérieur	5 7/8" inch
Epaisseur	41.275 mm
Epaisseur	1 5/8" inch
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE