

## Roulement conique 641-632-TIMKEN - 641-632-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/641-632-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Static <sup>(1)</sup> C <sub>0</sub>	Dynamic <sup>(2)</sup> C <sub>2</sub>	Static <sup>(2)</sup> C <sub>0</sub>	Dynamic <sup>(3)</sup> C <sub>3</sub>	Static <sup>(3)</sup> C <sub>0</sub>	Inner	Outer
mm	mm	mm	N	N	N	N	N	N		
66.675	136.525	41.275	27000	42100	71000	46000	1.61	29000	641	632
1.6250	5.3750	1.6265			18100	9900		67000		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>		
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sup>(2)</sup>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>(3)</sup>	A <sub>2</sub> <sup>(3)</sup>	Cage				kg	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				
41.275	35.390	-11.2	3.5	77.8	83.8	3.3	125.8	118.8	4.1	3.8	106.4	21.0	0.9814	2.72
1.6250	1.2900	-0.44	0.14	3.03	3.27	0.13	4.92	4.65	0.16	0.09				5.99

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952320168
Diam. intérieur	66.675 mm
Diam. extérieur	136.525 mm
Épaisseur	41.275 mm
Poids	2720 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE