

Roulement conique 77362-77675-TIMKEN - 77362-77675-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/77362-77675-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | | | | |
|--------------------|---------|---------|---------------------------------------|--------------------------------------|-------------------------|--|---------------------------------------|-------|-------------|--------|--------|-------|-------|
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C ₁ | Static ⁽²⁾ C ₀ | Factor ⁽³⁾ K | Dynamic ⁽⁴⁾ C ₉₀ | Static ⁽⁵⁾ C ₁₀ | Inner | Outer | | | | |
| mm | mm | mm | N | N | N | N | N | | | | | | |
| 92.075 | 171.450 | 47.625 | 94000 | 34600 | 3.37 | 1.63 | 89100 | 95300 | 1.58 | 474000 | 103000 | 77362 | 77675 |
| 3.6250 | 6.7500 | 1.8750 | | | | | 19800 | 12900 | | | | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|---|--------------------------------------|---|--------------------------------------|------------------------------------|-------------------------------|-------------------------------|------------------|----------------|----------------|----------------|-------|
| Shaft | | | | | Housing | | | | | G ₁ | G ₂ | C ₃ | | |
| Width B | Width C | ER. Dr. α ⁽¹⁾ | Max. Shaft Fillet Radius R ⁽²⁾ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ⁽³⁾ | Backing Shoulder Dia. D ₁ | Cage A ₁ ⁽⁴⁾ | A ₂ ⁽⁵⁾ | A ₃ ⁽⁶⁾ | | | | kg | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | |
| 48.280 | 38.190 | -5.7 | 3.5 | 103.0 | 105.8 | 3.3 | 161.8 | 158.8 | 3.4 | 1.8 | 256.2 | 37.7 | 0.1017 | 4.32 |
| 1.9000 | 1.5000 | -0.38 | 0.14 | 4.06 | 4.23 | 0.13 | 6.34 | 6.02 | 0.13 | 0.04 | | | | 10.41 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952323442 |
| Diam. intérieur | 92.075 mm |
| Diam. extérieur | 171.45 mm |
| Épaisseur | 47.625 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE