

Roulement conique 67983-67920-TIMKEN - 67983-67920-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/67983-67920-timken>

TAPERED ROLLER BEARINGS
SINGLE ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|-------------------------|-----------------------|-------|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ Y | Dynamic ⁽¹⁾ C ₂ | Factor ⁽²⁾ K | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | N | | N | | | |
| 203.200 | 282.575 | 46.038 | 92000 | 1.11 | 130000 | 1.15 | 87000 | 67983 | 67920 | |
| 8.0000 | 11.1250 | 1.8125 | 113000 | | 28300 | | 103000 | | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | | |
|--------------------|---------|--------------------------|---|--------------------------------------|--|--------------------------------------|-------------------------------|-------------------------------|-------------------------------|------------------|----------------|----------------|-------------------------------|-------------------------------|-------------------------------|
| Shaft | | | | | Housing | | | | | G ₁ | G ₂ | C ₃ | | | |
| Width B | Width C | ER. Dr. α ⁽¹⁾ | Max Shaft Fillet Radius R _{fs} | Backing Shoulder Dia. d _s | Max Housing Fillet Radius r ⁽²⁾ | Backing Shoulder Dia. D _s | A ₁ ⁽³⁾ | A ₂ ⁽³⁾ | A ₃ ⁽³⁾ | | | | A ₄ ⁽³⁾ | A ₅ ⁽³⁾ | A ₆ ⁽³⁾ |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm |
| 46.038 | 36.512 | 16.0 | 3.5 | 216.0 | 222.0 | 3.3 | 275.0 | 260.0 | 4.4 | 1.7 | 0.17 | 0.07 | 0.15 | 0.17 | 0.07 |
| 1.8125 | 1.4375 | 0.63 | 0.14 | 8.50 | 8.74 | 0.13 | 10.83 | 10.24 | 0.17 | 0.07 | 0.07 | 0.07 | 0.07 | 0.07 | 0.07 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3616060456885 |
| Diam. intérieur | 203.2 mm |
| Diam. extérieur | 282.575 mm |
| Épaisseur | 46.038 mm |
| Poids | 8710 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE