

## Roulement conique

### EE295950-295193-TIMKEN - EE295950-295193-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/ee295950-295193-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Factor <sup>(3)</sup> Y	Dynamic <sup>(1)</sup> C <sub>02</sub>	Factor <sup>(2)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N			N		N			
241.300	488.950	120.650	242000	0.31	1.02	628000	230000	1.87	3210000	EE295950	295193
5.500	19.250	4.750	54000			141000	75000		74000		

  

Bearing Dimensions										Geometry Factors			Bearing Weight																																											
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>																																										
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max. Shaft Fillet Radius R <sub>f1</sub>	Backing Shoulder Dia. d <sub>1s</sub>	Max. Housing Fillet Radius r <sub>1</sub> <sup>(2)</sup>	Backing Shoulder Dia. D <sub>1s</sub>	A <sub>1</sub> <sup>(3)</sup>	A <sub>2</sub> <sup>(3)</sup>	A <sub>3</sub> <sup>(3)</sup>				A <sub>4</sub> <sup>(3)</sup>		A <sub>5</sub> <sup>(3)</sup>	A <sub>6</sub> <sup>(3)</sup>	A <sub>7</sub> <sup>(3)</sup>	A <sub>8</sub> <sup>(3)</sup>	A <sub>9</sub> <sup>(3)</sup>	A <sub>10</sub> <sup>(3)</sup>	A <sub>11</sub> <sup>(3)</sup>	A <sub>12</sub> <sup>(3)</sup>	A <sub>13</sub> <sup>(3)</sup>	A <sub>14</sub> <sup>(3)</sup>	A <sub>15</sub> <sup>(3)</sup>	A <sub>16</sub> <sup>(3)</sup>	A <sub>17</sub> <sup>(3)</sup>	A <sub>18</sub> <sup>(3)</sup>	A <sub>19</sub> <sup>(3)</sup>	A <sub>20</sub> <sup>(3)</sup>	A <sub>21</sub> <sup>(3)</sup>	A <sub>22</sub> <sup>(3)</sup>	A <sub>23</sub> <sup>(3)</sup>	A <sub>24</sub> <sup>(3)</sup>	A <sub>25</sub> <sup>(3)</sup>	A <sub>26</sub> <sup>(3)</sup>	A <sub>27</sub> <sup>(3)</sup>	A <sub>28</sub> <sup>(3)</sup>	A <sub>29</sub> <sup>(3)</sup>	A <sub>30</sub> <sup>(3)</sup>	A <sub>31</sub> <sup>(3)</sup>	A <sub>32</sub> <sup>(3)</sup>	A <sub>33</sub> <sup>(3)</sup>	A <sub>34</sub> <sup>(3)</sup>	A <sub>35</sub> <sup>(3)</sup>	A <sub>36</sub> <sup>(3)</sup>	A <sub>37</sub> <sup>(3)</sup>	A <sub>38</sub> <sup>(3)</sup>	A <sub>39</sub> <sup>(3)</sup>	A <sub>40</sub> <sup>(3)</sup>	A <sub>41</sub> <sup>(3)</sup>	A <sub>42</sub> <sup>(3)</sup>	A <sub>43</sub> <sup>(3)</sup>	A <sub>44</sub> <sup>(3)</sup>	A <sub>45</sub> <sup>(3)</sup>	A <sub>46</sub> <sup>(3)</sup>
120.650	102.075	-31.8	0.4	276.0	285.0	0.4	408.5	446.0	18.0	4.8	2547.3	171.0	0.1864	183.07																																										
4.750	3.620	-1.22	0.25	10.87	11.22	0.25	17.74	17.48	0.73	0.16				221.24																																										

## CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952328171
Diam. intérieur	241.3 mm
Diam. extérieur	488.95 mm
Épaisseur	120.65 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE