


## Roulement conique

### HM265049-HM265010-TIMKEN - HM265049-HM265010-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/hm265049-hm265010-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Static <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(4)</sup> K	Dynamic <sup>(5)</sup> C <sub>10</sub>	Factor <sup>(6)</sup> K	Static <sup>(7)</sup> C <sub>2</sub>	Inner	Outer
mm	mm	mm	N		N		N		N		
368.249	523.875	101.600	227000	1.33	1.60	100000	230000	1.78	430000	HM265049	HM265010
14.698	20.6250	4.0003	113000			100000	75400		97000		

Bearing Dimensions										Geometry Factors			Bearing Weight					
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>				
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sub>1</sub> <sup>(2)</sup>	Backing Shoulder Dia. d <sub>s</sub> <sup>(3)</sup>	Max Housing Fillet Radius r <sub>1</sub> <sup>(4)</sup>	Backing Shoulder Dia. D <sub>s</sub> <sup>(5)</sup>	A <sub>1</sub> <sup>(6)</sup>	A <sub>2</sub> <sup>(7)</sup>	A <sub>3</sub> <sup>(8)</sup>				mm		mm	mm	mm	mm
101.600	79.375	-8.4	6.4	394.0	406.0	6.4	489.0	487.0	8.2	3.3	4257.3	412.9	0.2108	89.28	152.36			
4.0003	3.1250	-0.33	0.25	15.51	15.75	0.25	18.63	18.17	0.36	0.15								

## CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952329918
Diam. intérieur	368.249 mm
Diam. extérieur	523.875 mm
Épaisseur	101.6 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE