




Roulement à bille simple rangée ZKLN2557-2Z-INA - ZKLN2557-2Z-INA

<https://www.123roulement.be/roulement-palier/roulement-bille/simple-rangee/zkln2557-2z-ina>

Axial angular contact ball bearings ZKLN2557-2Z
double direction, gap seals on both sides

d	25 mm	Tolerance: -0.005
D	57 mm	Tolerance: -0.010
B	28 mm	Tolerance: -0.25
α	60 °	Contact angle
D_{max}	48 mm	
d₁	40.5 mm	
d₂	32 mm	
r_{1, max}	0.6 mm	
r_{2, max}	0.3 mm	
m	0.34 kg	Mass
C_d	27200 N	Basic dynamic load rating, axial
C_{0a}	50700 N	Basic static load rating, axial
n_{Grease}	4700 1/min	Limiting speed for grease lubrication
M_{fr}	0.2 Nm	Bearing frictional torque
S_{ax}	750 kg/m	Axial rigidity
q₀	200 1/mmrad	Tilting rigidity
M₀	0.486 kg x cm ²	Mass moment of inertia for rotating inner ring
r_{ax}	2 μm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZM25	Designation of recommended INA locknut
	AM25	Designation of recommended INA locknut
		Locknuts not included in delivery.
M_s	25 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
	9410 N	Axial preload force

CARACTÉRISTIQUES PRODUIT

Marque	INA
N° Ean13	3663952334882
Diam. intérieur	25 mm
Étanchéité	Flasque des deux côtés
Diam. extérieur	57 mm
Épaisseur	28 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE