

Roulement conique XA33116-Y33116-TIMKEN - XA33116-Y33116-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/xa33116-y33116-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • IsoClass

IsoClass

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic ⁽¹⁾ C ₁	Factor ⁽¹⁾ Y	Dynamic ⁽²⁾ C ₀	Factor ⁽²⁾ C _{0e}	Static C ₀	Assembly Inner/Outer		
mm	mm	mm	N		N	N	N			
in.	in.	in.	kN		kN	kN	kN			
80.000	130.000	37.000	247000	0.42	1.44	64100	45700	1.40	300000	67300
3.1496	5.1181	1.4567	55600			14400	10300		67300	15100

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					C ₁	C ₂	C ₃		
Width B	Width C	ER Dr. a ⁽¹⁾	Max Shaft Fillet Radius R ⁽¹⁾	Backing Shoulder Dia. d ₄	Max Housing Fillet Radius r ⁽²⁾	Backing Shoulder Dia. D ₄	Cap	A ₁ ⁽³⁾	A ₂ ⁽³⁾				G ₁	G ₂
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
in.	in.	in.	in.	in.	in.	in.	in.	in.	in.	in.	in.	in.	in.	in.
37.000	29.000	-0.1	0.0	89.0	0.0	1.5	125.0	118.0	2.4	2.5	121.0	37.0	0.000	1.85
1.4567	1.1417	-0.04	0.00	3.50	0.00	0.06	4.92	4.69	0.13	0.10	4.76	1.4567	0.000	4.10

CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952353647
Diam. intérieur	80 mm
Diam. extérieur	130 mm
Épaisseur	37 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE