

Roulement conique 30226-TIMKEN - 30226-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/30226-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • IsoClass

IsoClass

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|-------------------------|-----------------------|----------------------|-------------|--|
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ Y | Dynamic ⁽³⁾ C ₀ | Factor ⁽³⁾ K | Static C ₀ | Assembly Inner/Outer | | |
| mm | mm | mm | N | | N | N | N | | | |
| in | in | in | kN | | kN | kN | kN | | | |
| 130.000 | 230.000 | 43.750 | 431000 | 0.44 | 112000 | 83200 | 950000 | 30226 | | |
| 5.1181 | 9.0551 | 1.7224 | 96900 | | 25100 | 18700 | 124000 | | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | | |
|--------------------|---------|-------------------------|--|--------------------------------------|--|--|--------------------------------------|--|-------------------------------|-------------------------------|----------------|----------------|----------------|------|----|
| Shaft | | | | | Housing | | | | | Cage | | | | | |
| Width B | Width C | ER Co. a ⁽¹⁾ | Max Shift Fillet Radius R ⁽¹⁾ | Backing Shoulder Dia. d _s | Backing Fillet Radius r ⁽¹⁾ | Max Housing Fillet Radius R ⁽¹⁾ | Backing Shoulder Dia. D _s | Backing Fillet Radius r ⁽¹⁾ | A ₁ ⁽¹⁾ | A ₂ ⁽¹⁾ | G ₁ | G ₂ | C ₂ | kg | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | lb |
| 40.000 | 34.000 | 2.0 | 4.0 | 140.0 | 100.0 | 3.0 | 217.0 | 200.0 | 2.0 | 1.1 | 287.4 | 77.3 | 0.1118 | 7.90 | |
| 1.5748 | 1.3388 | 0.08 | 0.16 | 5.51 | 3.94 | 0.12 | 8.54 | 7.87 | 0.08 | 0.04 | 11.29 | 3.04 | 0.0044 | 0.17 | |

CARACTÉRISTIQUES PRODUIT

| | |
|------------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952354002 |
| Diam. intérieur | 130 mm |
| Diam. extérieur | 230 mm |
| Epaisseur | 43.75 mm |
| Poids | 7060 g |
| Charge dynamique | 112 kN |
| Charge statique | 83.2 kN |
| Conditionnement | 1 |
| Norme | Sans norme |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE