

## Roulement conique 32930-TIMKEN - 32930-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/32930-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(1)</sup> Y	Dynamic <sup>(2)</sup> C <sub>0</sub>	Factor <sup>(2)</sup> K	Static C <sub>0</sub>	Assembly	Inner/Outer	
mm	mm	mm	N		N		N			
150.000	210.000	38.000	324000	1.33	1.83	84000	4700	1.78	57000	2030
5.906	8.267	1.496	12850			1830	1600		12500	

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER Co. a <sup>(1)</sup>	Max Shift Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>4</sub>	Backing Shoulder Dia. d <sub>6</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>1</sub>	Backing Shoulder Dia. D <sub>2</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>2</sub>	kg
38.000	38.000	-1.5	2.5	160.0	160.0	2.0	200.0	197.0	1.5	2.0	428.9	151.2	0.1167	3.89
1.496	1.496	-0.06	0.10	6.30	6.30	0.08	7.92	7.76	0.06	0.10				0.02

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952354040
Diam. intérieur	150 mm
Diam. intérieur	5.906" inch
Diam. extérieur	210 mm
Diam. extérieur	8.268" inch
Epaisseur	38 mm
Epaisseur	1.496" inch
Poids	4000 g
Conditionnement	1
Norme	Sans norme

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE