

## Roulement conique 32940-TIMKEN - 32940-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/32940-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(1)</sup> Y	Dynamic <sup>(2)</sup> C <sub>0</sub>	Factor <sup>(2)</sup> K	Static C <sub>0</sub>	Assembly Inner/Outer		
mm	mm	mm	N		N	N	N			
200.000	280.000	51.000	501000	1.33	145000	18300	1.48	1050000	23940	
7.8740	11.0236	2.0079	126500		32700	22100		255000		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>2</sub>
Width B	Width C	ER Co. a <sup>(1)</sup>	Max Shift Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Backing Shoulder Dia. D <sub>s</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>s</sub>	Backing Shoulder Dia. D <sub>s</sub>	Capo A <sub>1</sub> <sup>(1)</sup>				Capo A <sub>2</sub> <sup>(1)</sup>	
51.000	26.000	3.0	3.0	213.0	213.0	2.5	213.0	262.0	4.6	1.6	90.3	226.2	0.129	0.45
2.0079	1.0204	0.12	0.12	8.39	8.34	0.10	8.37	10.21	0.18	0.08				0.46

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952354125
Diam. intérieur	200 mm
Diam. extérieur	280 mm
Épaisseur	51 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE