


Douille à aiguilles TLAM3018-IKO - TLAM3018-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/tlam3018-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



Shaft dia. mm	Identification number												
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g				
30	---	---	---	---	---	---	---	---	---				
								TLAM 3018 40					
Boundary dimensions mm		Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring		
F _w	D	C	i ₂ Max.	Shaft dia. H7		Housing bore dia. H7		N	N				
30	37	18	2.8	Max.	Min.	Max.	Min.	N	N				
				30.000	29.987	---	---	36.992	36.987	16 400	29 800	12 000	---

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952355115
Diam. intérieur	30 mm
Diam. extérieur	37 mm
Épaisseur	18 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE