

## Roulement conique 390-394D-TIMKEN - 390-394D-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/390-394d-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDD

**TYPE TDD**

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic C <sub>10</sub>	Factor Y <sub>1</sub>	Factor Y <sub>2</sub>	C <sub>0</sub>	Dynamic C <sub>90</sub>	C <sub>50</sub>	Factor K	
mm	mm	mm	mm	N			N	N	N		
57.150	110.000	52.388	48.828	12500	0.40	1.58	2.50	25000	17000	44000	
2.2500	4.3307	2.0625	1.9125	38700				5700	3970	10300	

  

Part Number		Dimensions				Pin		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>1</sub>	K <sub>1</sub>	K <sub>2</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	kg
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
390	394D	2.3	70.0	0.8	106.4	-	-	50.0	21.4	0.0064	2.88
		0.09	2.75	0.03	4.11						4.58

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952356730
Diam. intérieur	57.15 mm
Diam. extérieur	110 mm
Épaisseur	52.388 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE