

## Roulement conique 477-472D-TIMKEN - 477-472D-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/477-472d-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDD

**TYPE TDD**

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic <sup>(1)</sup> C <sub>10</sub>	Static <sup>(1)</sup> C <sub>0</sub>	Factor <sup>(2)</sup> Y <sub>1</sub>	Factor <sup>(2)</sup> Y <sub>2</sub>	Dynamic <sup>(3)</sup> C <sub>90</sub>	Static <sup>(3)</sup> C <sub>0</sub>	Factor <sup>(3)</sup> K	
mm	mm	mm	mm	N	N	N	N	N	N	N	
63.508	120.008	65.098	53.825	25000	34700	0.38	1.75	2.61	37200	44700	
2.500	4.7244	2.5628	2.1299						8300	10000	

  

Part Number		Shaft				Housing				Pin		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>s</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>s</sub>	K <sub>a</sub>	K <sub>b</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	C <sub>2</sub>	C <sub>3</sub>	kg		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm		
477	472D	0.8	23.0	0.8	194.0	-	-	77.2	23.0	0.1080	3.25	7.17			
		0.03	2.87	0.03	4.48	-	-								

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952357010
Diam. intérieur	63.5 mm
Diam. extérieur	120 mm
Épaisseur	65.09 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE