

Roulement conique 395-S-394D-TIMKEN - 395-S-394D-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/395-s-394d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDD

TYPE TDD

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic ⁽¹⁾ C ₁₀	Factor ⁽²⁾ Y ₁	Y ₂	C ₀	Dynamic ⁽¹⁾ C ₉₀	Factor ⁽²⁾ C ₂₀₀	K	
mm	mm	mm	mm	N			N	N	N		
66.675	110.000	52.388	46.828	17500	0.40	1.68	2560	1700	4600	1.45	
2.6250	4.3307	2.0625	1.8129	38700			5700	3970	10300		

Part Number		Shaft				Housing				Pin		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R _f	Backing Shoulder Dia. d _s	Max. Housing Fillet Radius r _h	Backing Shoulder Dia. D _s	K ₁	K ₂	G ₁	G ₂	C ₁	C ₂			kg	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm			mm	
395-S	394D	3.5 0.14	79.0 3.11	8.8 0.35	106.4 4.11	-	-	50.0	21.4	0.0864				1.26 3.88	

CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952357164
Diam. intérieur	66.675 mm
Diam. extérieur	110 mm
Épaisseur	52.388 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE