

Roulement conique 642-632D-TIMKEN - 642-632D-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/642-632d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDD

TYPE TDD

| Bearing Dimensions | | | | Load Ratings | | | | | | | |
|--------------------|---------|---------|---------------------------|--|--------------------------------------|----------------|----------------|--|--|-------------------------|--|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic ⁽¹⁾ C ₁₀ | Factor ⁽²⁾ Y ₁ | Y ₂ | C ₀ | Dynamic ⁽¹⁾ C ₉₀ | Factor ⁽²⁾ C ₀₂₀ | Factor ⁽²⁾ K | |
| mm | mm | mm | mm | N | | | N | N | N | | |
| 68.282 | 136.525 | 95.250 | 76.200 | 40600 | 0.30 | 1.86 | 2.78 | 60400 | 37400 | 105000 | |
| 2.6875 | 5.3750 | 3.7500 | 3.0000 | 91200 | | | | 13600 | 8400 | 23600 | |

| Part Number | | Shaft | | | | Housing | | | | Pin | | Geometry Factors | | | Bearing Weight |
|-------------|-------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|----------------|----------------|----------------|----------------|------------------|----------------|----|----------------|
| Inner | Outer | Max. Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ₁ | Backing Shoulder Dia. D ₁ | K ₁ | K ₂ | G ₁ | G ₂ | C ₁ | G ₃ | G ₄ | C ₂ | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | kg | |
| 642 | 632D | 3.5 | 85.0 | 1.5 | 125.0 | - | - | 105.4 | 21.0 | 0.3814 | 5.83 | 13.04 | | | |
| | | 0.14 | 3.35 | 0.06 | 4.92 | - | - | | | | | | | | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952357201 |
| Diam. intérieur | 66.675 mm |
| Diam. extérieur | 136.525 mm |
| Épaisseur | 95.25 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE