


Douille à aiguilles TA6030-Z-IKO - TA6030-Z-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/ta6030-z-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
60	TA	6030 Z	191	—	—	—	—	—	—	—

Boundary dimensions mm			Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring
F _w	D	C	Shaft dia. d ₁		Housing bore dia. D ₂		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring		
Max.	Max.	Max.	Max.	Min.	Max.	Min.	N	N	rpm	IRT 5030		
60	72	30	60.000	59.981	72.018	71.988	—	—	66 300	139 000	5 000	IRT 5030

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952357409
Diam. intérieur	60 mm
Diam. extérieur	72 mm
Épaisseur	30 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE