

Roulement conique 590-592D-TIMKEN - 590-592D-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/590-592d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDD

TYPE TDD

| Bearing Dimensions | | | | Load Ratings | | | | | | | |
|--------------------|---------|---------|---------------------------|-------------------------|-----------------------|-----------------------|----------------|-------------------------|-----------------|----------|--|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic C ₁₀ | Factor Y ₁ | Factor Y ₂ | C ₀ | Dynamic C ₉₀ | C ₅₀ | Factor K | |
| mm | mm | mm | mm | N | | | N | N | N | | |
| 79.985 | 152.400 | 82.550 | 63.500 | 37600 | 0.44 | 1.53 | 2.27 | 96000 | 42400 | 9700 | |
| 3.1480 | 6.0000 | 3.2500 | 2.5000 | 84500 | | | | 12000 | 9530 | 21000 | |

| Part Number | | Dimensions | | | | Pin | | Geometry Factors | | | Bearing Weight |
|-------------|-------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|------------------|----------------|----------------|----------------|
| Inner | Outer | Max. Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius R ₂ | Backing Shoulder Dia. D ₁ | K ₁ | K ₂ | G ₁ | G ₂ | C ₁ | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm |
| 590 | 592D | 3.5 | 98.0 | 8.8 | 146.0 | - | - | 111.4 | 38.3 | 0.1416 | 4.48 |
| | | 0.14 | 3.80 | 0.35 | 5.67 | | | | | | 9.87 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952358147 |
| Diam. intérieur | 79.985 mm |
| Diam. extérieur | 152.4 mm |
| Épaisseur | 82.55 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE