

Roulement conique 95475-95927CD-TIMKEN - 95475-95927CD-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/95475-95927cd-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDD

TYPE TDD

| Bearing Dimensions | | | | Load Ratings | | | | | | | | |
|--------------------|---------|---------|---------------------------|------------------------|-----------------|-----------------------|----------------|------------------------|-----------------|-----------------------|--------|------|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic ⁽¹⁾ | | Factor ⁽²⁾ | | Dynamic ⁽¹⁾ | | Factor ⁽²⁾ | | |
| mm | mm | mm | mm | C ₁₀ | C ₉₀ | Y ₁ | Y ₂ | C ₁₀ | C ₉₀ | C ₅₀ | K | |
| 120.650 | 234.950 | 142.875 | 114.300 | 1100000 | 240000 | 0.37 | 1.83 | 2.72 | 163000 | 103000 | 264000 | 1.58 |
| 4.750 | 9.250 | 5.625 | 4.500 | | | | | | 30700 | 23200 | 83000 | |

| Part Number | | Dimensions | | | | Pin | | Geometry Factors | | | Bearing Weight |
|-------------|---------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|------------------|----------------|----------------|----------------|
| Inner | Outer | Max. Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ₁ | Backing Shoulder Dia. D ₁ | K ₁ | K ₂ | G ₁ | G ₂ | C ₁ | |
| 95475 | 95927CD | 6.4 | 148.8 | 1.5 | 217.8 | 22.23 | 8.73 | 453.9 | 15.4 | 0.1323 | 26.75 |
| | | 0.25 | 5.87 | 0.06 | 8.54 | 0.88 | 0.34 | | | | 58.02 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952359533 |
| Diam. intérieur | 120.65 mm |
| Diam. extérieur | 234.95 mm |
| Épaisseur | 142.875 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE