

Roulement conique 95500-95927CD-TIMKEN - 95500-95927CD-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/95500-95927cd-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDO

TYPE TDO

| Bearing Dimensions | | | | Load Ratings | | | | | | | |
|--------------------|---------|---------|---------------------------|--------------------------------------|-------------------------------------|----------------|-----------------|--------------------------------------|------------------|------------------------|--|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynami ¹⁾ C ₁₀ | Factor ²⁾ Y ₁ | Y ₂ | C ₉₀ | Dynami ³⁾ C ₅₀ | C _{50a} | Factor ⁴⁾ K | |
| mm | mm | mm | mm | N | | | N | N | N | | |
| 127.000 | 234.950 | 142.875 | 114.300 | 1090000 | 0.57 | 1.83 | 2.72 | 163000 | 103000 | 294000 | |
| 5.000 | 9.250 | 5.8250 | 4.5000 | 240000 | | | | 30700 | 23200 | 83000 | |

| Part Number | | Dimensions | | | | | | Pin | | | Geometry Factors | | | Bearing Weight |
|-------------|---------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|----------------|----------------|----------------|------------------|-------|----|----------------|
| Inner | Outer | Max. Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ₁ | Backing Shoulder Dia. D ₁ | K ₁ | K ₂ | G ₁ | G ₂ | C ₁ | C ₂ | | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | kg | |
| 95500 | 95927CD | 6.4 | 154.8 | 1.5 | 217.8 | 22.23 | 8.73 | 453.9 | 151.4 | 0.1323 | 26.36 | 55.88 | | |
| | | 0.25 | 6.30 | 0.06 | 8.54 | 0.88 | 0.34 | | | | | | | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952359649 |
| Diam. intérieur | 127 mm |
| Diam. extérieur | 234.95 mm |
| Épaisseur | 142.875 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE