


Douille à aiguilles YB98-IKO - YB98-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/yb98-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
14.288 ($\frac{9}{16}$)	—	—	—	—	—	—	—	—	YB 98 10.1
Boundary dimensions mm(inch)		Standard mounting dimensions mm			Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring	
F_w	D	C	d_2	Shaft dia. h_8	Housing bore dia. J_7	C	C_0	Allowable rotational speed ⁽¹⁾	
14.288 $\frac{9}{16}$	19.050 $\frac{3}{4}$	12.700 500	—	14.288 Max.	14.277 Min.	19.062 Max.	19.041 Min.	11 600 N	20 400 N
								11 000 rpm	RB 68

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952361604
Diam. intérieur	14.288 mm
Diam. extérieur	19.05 mm
Épaisseur	12.7 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE