


## Douille à aiguilles BHAM1212-IKO - BHAM1212-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/bham1212-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



| Shaft dia.<br>mm<br>(inch) | Identification number |                     |               |                                 |  |                     |            |                              |  |   |                         |
|----------------------------|-----------------------|---------------------|---------------|---------------------------------|--|---------------------|------------|------------------------------|--|---|-------------------------|
|                            | Standard              | Mass<br>(Ref.)<br>g | Closed end    | Mass<br>(Ref.)<br>g             | Standard                               | Mass<br>(Ref.)<br>g | Closed end | Mass<br>(Ref.)<br>g          | Grease retained<br>Mass<br>(Ref.)<br>g |   |                         |
| 19.050<br>(3/4)            | —                     | —                   | —             | —                               | —                                      | —                   | —          | BHAM 1212                    | 28.5                                   | —   | —                       |
| Boundary dimensions        |                       | mm(inch)            |               | Standard mounting dimensions    |  | mm                  |            | Basic dynamic<br>load rating | Basic static<br>load rating            | Allowable<br>rotational<br>speed <sup>(1)</sup> | Assembled<br>inner ring |
| $F_w$                      | $D$                   | $C$                 | $r_2$<br>Max. | Shaft dia.<br>h6<br>Max.   Min. | Housing bore dia.<br>J7<br>Max.   Min. | $C$                 | $C_0$      | N                            | N                                      | rpm   | IRB 812-1               |
| 19.050   1/4               | 26.988   1/2          | 19.05   .750        | 1.3           | 19.050   19.037                 | 27.000   26.979                        | 16 800              | 22 600     | 20 000                       | 20 000                                 |   |                         |

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | IKO           |
| N° Ean13        | 3663952361819 |
| Diam. intérieur | 19.05 mm      |
| Diam. intérieur | 3/4" inch     |
| Diam. extérieur | 26.988 mm     |
| Diam. extérieur | 1 1/16" inch  |
| Epaisseur       | 19.05 mm      |
| Epaisseur       | 3/4" inch     |
| Conditionnement | 1             |

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE