


Douille à aiguilles YB2016-IKO - YB2016-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/yb2016-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
31.750 (1 1/4)	—	—	—	—	—	—	—	—	YB 2016 57
Boundary dimensions mm(inch)		Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring	
<i>F_w</i>	<i>D</i>	<i>C</i>	<i>t₁</i>	Shaft dia. h ₈ Max. Min.	Housing bore dia. j7 Max. Min.	N	N	rpm	IRB 1616
31.750 1/4	38.100 1 1/2	25.40 1.000	—	31.750 31.734 38.114 38.089	—	40 900	100 000	4 500	IRB 1616

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952362359
Diam. intérieur	31.75 mm
Diam. intérieur	1 1/4" inch
Diam. extérieur	38.1 mm
Diam. extérieur	1 1/2" inch
Epaisseur	25.4 mm
Epaisseur	1" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE