


Douille à aiguilles BAM228-IKO - BAM228-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/bam228-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
34.925 (1 3/8)	---	---	---	---	---	---	---	BAM 228	29	---	---	---	---
Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynam. load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring				
F _w	D	C	f ₁	Shaft dia. h8	Housing bore dia. J7								
34.925	41.275	12.70	2.8	34.925	34.909	41.289	41.264	9 770	16 600	10 000	IRB 188		

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952363035
Diam. intérieur	34.925 mm
Diam. extérieur	41.275 mm
Épaisseur	12.7 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE