

Roulement conique

M667944-M667911D-TIMKEN - M667944-M667911D-TIMKEN

https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/m667944-m667911d-timken

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDD

TYPE TDD

| Bearing Dimensions | | | | Load Ratings | | | | | | | |
|--------------------|---------|---------|---------------------------|-------------------------|-----------------------|-----------------------|----------------|-------------------------|-----------------|----------|--|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic C ₁₀ | Factor Y ₁ | Factor Y ₂ | C ₀ | Dynamic C ₉₀ | C ₅₀ | Factor K | |
| mm | mm | mm | mm | N | | | N | N | N | | |
| 406.400 | 546.100 | 185.738 | 147.628 | 325000 | 0.42 | 1.52 | 2.41 | 484000 | 348000 | 863000 | |
| 18.000 | 21.500 | 7.3125 | 5.8125 | 731000 | | | | 109000 | 77800 | 190000 | |

| Part Number | | Dimensions | | | | Pin | | Geometry Factors | | | Bearing Weight |
|-------------|----------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|------------------|----------------|----------------|----------------|
| Inner | Outer | Max. Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ₁ | Backing Shoulder Dia. D ₁ | K ₁ | K ₂ | G ₁ | G ₂ | C ₁ | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | kg |
| M667944 | M667911D | 6.4 | 438.8 | 1.5 | 126.7 | - | - | 4026.7 | 498.9 | 0.2216 | 118.91 |
| | | 0.25 | 17.24 | 0.06 | 20.74 | - | - | | | | 282.18 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952364155 |
| Diam. intérieur | 406.4 mm |
| Diam. extérieur | 546.1 mm |
| Epaisseur | 185.738 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE