

Roulement à aiguilles GTRI7510845-IKO - GTRI7510845-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gtri7510845-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Inner Ring

| Shaft dia. mm | Identification number | | | | | | Mass (Ref.) g | d | | | |
|------------------------|-----------------------|---------------------------------|--------------------|------------------|-----------------------------|---|---|----------------------|---------|-------|-------------|
| | NA 49 | NA 69 | NA 48 | TAFI | TRI | GTRI | | | | | |
| 75 | --- | --- | --- | --- | --- | GTRI 7510845 | 1 440 | 75 | | | |
| Boundary dimensions mm | | Standard mounting dimensions mm | | | Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽¹⁾ | Assembled inner ring | | | |
| D | C | B | r _s min | r _w S | Min. d _s | Max. d _s | D _s Max. | N | N | rpm | LRTZ 756345 |
| 108 | 45 | 45.5 | 1 | 83 | 80 | 81 | 103 | 190 000 | 396 000 | 1 800 | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952372525 |
| Diam. intérieur | 75 mm |
| Diam. intérieur | 2.953" inch |
| Diam. extérieur | 108 mm |
| Diam. extérieur | 4.252" inch |
| Epaisseur | 45 mm |
| Epaisseur | 1.772" inch |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE