


Roulement à aiguilles NA4852-IKO - NA4852-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/na4852-iko>



| Shaft dia. mm | Identification number | | | | | | Mass (Ref.) | |
|------------------|-----------------------|-------|----------------|------|-----|------|-------------|-----|
| | NA 49 | NA 69 | NA 48 | TAFI | TRI | GTRI | g | d |
| 260 | — | — | NA 4852 | — | — | — | 11 000 | 260 |

| Boundary dimensions mm | | | | Standard mounting dimensions mm | | | Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ^(*) | Assembled inner ring | | |
|------------------------|----|---|-----------------------------------|---------------------------------|------------------|---------------------|-----------------------------|---|---|----------------------|-------|--------------|
| D | C | B | r _{s min} ⁽¹⁾ | F _w ⁽²⁾ | S ⁽³⁾ | Min. d _s | Max. d _s | N | N | rpm | | |
| 320 | 60 | — | 2 | 285 | 2 | 269 | 282 | 311 | 354 000 | 1 220 000 | 1 100 | LRT 26028560 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952373201 |
| Diam. intérieur | 260 mm |
| Diam. intérieur | 10.236" inch |
| Diam. extérieur | 320 mm |
| Diam. extérieur | 12.598" inch |
| Epaisseur | 60 mm |
| Epaisseur | 2.362" inch |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE