


Roulement à aiguilles GBRI102216-IKO - GBRI102216-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbri102216-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
15.875 (5/8)	GBRI 102216	133	15.875 (5/8)	34.925 (1 3/8)	25.400 (1)	25.650	22.225 (7/8)

Standard mounting dimensions mm		Static load rating C ₀	Basic load rating C ₀	Allowable rotational speed (1) rpm	Assembled inner ring		
d _a Min.	d _a Max.	r _{as} mm	N	N			
21	21.2	30	0.6 ⁽²⁾	38 300	58 300	7 000	LRBZ 101416

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377407
Diam. intérieur	15.875 mm
Diam. intérieur	5/8" inch
Diam. extérieur	34.925 mm
Diam. extérieur	1 3/8" inch
Epaisseur	25.65 mm
Epaisseur	1.01" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE