


Roulement à aiguilles GBRI122412-IKO - GBRI122412-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbri122412-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
19.050 (3/4)	GBRI 122412	112	19.050 ± 0.010	38.100 ± 0.010	19.050 ± 0.010	19.300	25.400 ± 0.010

Standard mounting dimensions mm		Ball diam. mm (inch)	Basic rating C ₀	Allowable rotational speed (P)	Assembled inner ring		
Min.	Max.	r _{max}	N	N	rpm		
24	24.4	33.3	0.6 ⁽¹⁾	31 000	46 100	6 000	LRBZ 121612

Notes:
(1) Maximum permissible corner radius of the housing.
(P) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
3. No grease is pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377414
Diam. intérieur	19.05 mm
Diam. intérieur	3/4" inch
Diam. extérieur	38.1 mm
Diam. extérieur	1 1/2" inch
Epaisseur	19.3 mm
Epaisseur	0.76" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE