


Roulement à aiguilles GBRI122416-IKO - GBRI122416-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbri122416-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
19.050 ($\frac{3}{4}$)	GBRI 122416	150	19.050 $\frac{J_2$	38.100 $\frac{J_2$	25.400 $\frac{J_1}$	25.650	25.400 $\frac{J_1}$

Standard mounting dimensions mm		Ball/needle lead angle C	Basic static load rating C_0	Allowable rotational speed $(^{\circ})$	Assembled inner ring		
Min.	Max.	$r_{as max}$	N	N	rpm		
24	24.4	33.3	0.6 $^{\circ}$	41 400	67 100	6 000	LRBZ 121616

Notes: ⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377421
Diam. intérieur	19.05 mm
Diam. extérieur	38.1 mm
Épaisseur	25.65 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE