


Roulement à aiguilles GBRI223520-IKO - GBRI223520-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbri223520-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
34.925 (1 3/8)	GBRI 223520	316	34.925 ± 0.015	55.562 ± 0.025	31.750 ± 0.025	32.000	41.275 ± 0.025

Standard mounting dimensions mm		Sub-dynamic load rating C ₁₀ N	Basic static load rating C ₀ N	Allowable rotational speed (F) rpm	Assembled inner ring LRBZ 222620		
d _a Min.	d _a Max.						
40.2	40.2	50.5	0.5	67 000	130 000	3 500	LRBZ 222620

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377490
Diam. intérieur	34.925 mm
Diam. extérieur	55.562 mm
Épaisseur	32 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE