

Roulement à aiguilles GBRI264116-IKO - GBRI264116-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbri264116-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
41.275 (1 5/8)	GBRI 264116	350	41.275 (1 5/8)	65.088 (2 5/8)	25.400 (1)	25.650	50.800 (2)
Standard mounting dimensions mm		Sub-dynamic load rating C_0	Basic load rating C_0	Allowable rotational speed (°)	Assembled inner ring		
d_a	D_a				$r_{as\ max}$	$r_{is\ max}$	$r_{is\ max}$
Min.	Max.	N	N	rpm			
48	49	59.2	1	63 100	130 000	3 000	LRBZ 263216

Notes: (°) Maximum permissible corner radius of the housing.
(°) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377537
Diam. intérieur	41.275 mm
Diam. intérieur	1 5/8" inch
Diam. extérieur	65.088 mm
Diam. extérieur	2 9/16" inch
Epaisseur	25.65 mm
Epaisseur	1.01" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE