

Roulement à aiguilles GBR364824-IKO - GBR364824-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbr364824-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F	D	C	D_s Max.	$r_{as\ max}$
57.150 (2 1/4)	GBR 364824	490	57.150 (1 1/2)	76.200 (3)	38.100 (1 1/2)	69.2	1.5
Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm					
113 000	224 000	2 500					

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 2. The outer ring has an oil groove and an oil hole.
3. No grease is pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377551
Diam. intérieur	57.15 mm
Diam. intérieur	2 1/4" inch
Diam. extérieur	76.2 mm
Diam. extérieur	3" inch
Epaisseur	38.1 mm
Epaisseur	1 1/2" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE