

Roulement à aiguilles GBR405228-IKO - GBR405228-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbr405228-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series

| Shaft dia. mm (inch) | Identification number | Mass (ref.) g | Boundary dimensions mm(inch) | | | Standard mounting dimensions mm ⁽¹⁾ | |
|-----------------------------------|---|--|------------------------------|----------------|----------------|---|---------------------|
| | | | F | D | C | D _s Max. | r _{as max} |
| 63.500 (2 1/2) | GBR 405228 | 635 | 63.500 (2 1/2) | 82.550 (3 1/2) | 44.450 (1 3/4) | 75.7 | 1.5 |
| Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽²⁾ N | | | | | |
| N | N | rpm | | | | | |
| 141 000 | 306 000 | 2 500 | | | | | |

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952377582 |
| Diam. intérieur | 63.5 mm |
| Diam. extérieur | 82.55 mm |
| Épaisseur | 44.45 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE