

## Roulement à aiguilles GBR648032-IKO - GBR648032-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbr648032-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm <sup>(1)</sup>	
			$F$	$D$	$C$	$D_s$ Max.	$r_{as\ max}$
<b>101.600</b> (4)	<b>GBR 648032</b>	1 500	101.600 (4)	127.000 (5)	50.800 (2)	119	1.5
Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(3)</sup> $n$ rpm					
237 000	556 000	1 500					

Notes:<sup>(1)</sup> Maximum permissible corner radius of the housing.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks:  
2. The outer ring has an oil groove and an oil hole.  
3. No grease is pre-packed. Perform proper lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377674
Diam. intérieur	101.6 mm
Diam. extérieur	127 mm
Épaisseur	50.8 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE