

Roulement à aiguilles GBR162412-IKO - GBR162412-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbr162412-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F	D	C	D_s Max.	$r_{as\ max}$
25.400 (1)	GBR 162412	79	25.400 ⁽¹⁾	38.100 ⁽¹⁾	19.050 ⁽²⁾	33.3	0.6
Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽³⁾ n rpm					
N	N	N					
31 000	46 100	6 000					

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
3. No grease is pre-applied. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377735
Diam. intérieur	25.4 mm
Diam. extérieur	38.1 mm
Épaisseur	19.05 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE