

## Roulement à aiguilles GBR182616-IKO - GBR182616-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbr182616-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm <sup>(1)</sup>	
			$\bar{F}_w$	D	C	$D_s$ Max.	$r_{as\ max}$
28.575 (1 1/8)	GBR 182616	117	28.575 (1 1/8)	41.275 (1 1/2)	25.400 (1)	36.3	0.6
Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm					
43 900	75 300	5 500					

Notes:  
(1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-packed. Perform proper lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377759
Diam. intérieur	28.575 mm
Diam. intérieur	1 1/8" inch
Diam. extérieur	41.275 mm
Diam. extérieur	1 5/8" inch
Epaisseur	25.4 mm
Epaisseur	1" inch
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE