

Roulement à aiguilles GBR202816-IKO - GBR202816-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbr202816-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F	D	C	D _s Max.	r _{as max}
31.750 (1 1/4)	GBR 202816	128	31.750 (1 1/4)	44.450 (1 3/4)	25.400 (1)	39.6	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾ N	N	N	rpm		
46 600	83 900	4 500					

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377766
Diam. intérieur	31.75 mm
Diam. extérieur	44.45 mm
Épaisseur	25.4 mm
Poids	133 g
Conditionnement	-
Norme	-

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE