


Roulement à aiguilles GBRI325224-IKO - GBRI325224-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbri325224-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
50.800 (2)	GBRI 325224	870	50.800 2	82.550 3 1/2	38.100 1 1/2	38.350	63.500 1 1/2

Standard mounting dimensions mm		Ball diam. mm C	Basic load rating C_0 N	Allowable rotational speed (P) rpm	Assembled inner ring LRBZ 324024		
d_a Min.	d_a Max.						
58	61	75.7	1.5	120 000	248 000	2 500	LRBZ 324024

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377896
Diam. intérieur	50.8 mm
Diam. extérieur	82.55 mm
Épaisseur	38.1 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE