


## Roulement à aiguilles GBRI365628-IKO - GBRI365628-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbri365628-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			$d$	$D$	$C$	$B$	$F_w$
57.150 (2 1/4)	GBRI 365628	1 130	57.150 $\pm$ 0.02	88.900 $\pm$ 0.02	44.450 $\pm$ 0.02	44.700	69.850 $\pm$ 0.02

Standard mounting dimensions mm			Sub-dynamic load rating $C_1$ N	Basic load rating $C_0$ N	Allowable rotational speed (1) rpm	Assembled inner ring LRBZ 364428
$d_a$ Min.	$d_a$ Max.	$r_{as\ max}$ Max.				
65	67	82	1.5	147 000	336 000	2 000

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-packed. Perform proper lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377926
Diam. intérieur	57.15 mm
Diam. extérieur	88.9 mm
Épaisseur	44.45 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE