


Roulement à aiguilles RNA6905-U-IKO - RNA6905-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/rna6905-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_a (1)
30	—	—	—	RNA 6905U	111	30	42	30	0.3
Standard rounding dimension D_s Max. mm	N	N	N						
Basic dynamic load rating C	39 200	58 700	58 700						
Basic static load rating C_0									
Allowable rotational speed (2)									

Notes: (1) Minimum allowable value of chamfer dimension r . Allowable rotational speed applies to grease lubrication. The outer ring has an oil groove and an oil hole.
Remarks: 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952379036
Diam. intérieur	30 mm
Diam. intérieur	1.181" inch
Diam. extérieur	42 mm
Diam. extérieur	1.654" inch
Epaisseur	30 mm
Epaisseur	1.181" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE