

## Roulement à aiguilles RNA49-28-U-IKO - RNA49-28-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/rna49-28-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

| Shaft dia.<br>mm                                      | Identification number                    |   |  |               | Mass<br>(Ref.)<br>g | Boundary dimensions<br>mm |     |     |           |
|---|--|---|--|---------------|---------------------|---------------------------|-----|-----|-----------|
|   | With two seals                           | With one seal                             | With two seals                             | With one seal |                     | $F_w$                     | $D$ | $C$ | $r_a$ (1) |
| 32  | ---                                      | <b>RNA 49/28U</b>                         | ---  | ---           | 75.5                | 32                        | 45  | 17  | 0.3       |
| Standard rounding<br>dimension<br>$D_s$<br>Max.<br>mm |  |   |  |               |                     |                           |     |     |           |
|   | Basic dynamic<br>load rating<br>$C$<br>N | Basic static<br>load rating<br>$C_0$<br>N | Allowable<br>rotational<br>speed(2)<br>rpm |               |                     |                           |     |     |           |
| 43  | 21 000                                   | 26 800                                    | 6 000                                      |               |                     |                           |     |     |           |

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | IKO           |
| N° Ean13        | 3663952379067 |
| Diam. intérieur | 32 mm         |
| Diam. intérieur | 1.26" inch    |
| Diam. extérieur | 45 mm         |
| Diam. extérieur | 1.772" inch   |
| Epaisseur       | 17 mm         |
| Epaisseur       | 0.669" inch   |
| Conditionnement | 1             |

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE