

## Roulement à aiguilles RNA69-28-U-IKO - RNA69-28-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/rna69-28-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_a$ (1)
32	—	—	—	RNA 69/28U	133	32	45	30	0.3
Standard rounding dimension $D_s$ Max. mm		Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed(2) rpm					
43		38 900	59 100	6 000					

Notes: (1) Minimum allowable value of chamfer dimension  $r_a$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952379074
Diam. intérieur	32 mm
Diam. intérieur	1.26" inch
Diam. extérieur	47 mm
Diam. extérieur	1.85" inch
Epaisseur	30 mm
Epaisseur	1.181" inch
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE