

Roulement à aiguilles RNA6906-U-IKO - RNA6906-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/rna6906-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|--|---------------------------------------|---------------|--|---------------------------------------|---------------------|---------------------------|-----|-----|-----------|
| | With two seals | With one seal | With two seals | With one seal | | F_w | D | C | r_s (1) |
| 16 | — | — | — | RNA 6906U | 125 | 35 | 47 | 30 | 0.3 |
| Standard mounting diameter D_s Max. mm | 40 | 100 | 63 000 | 5 500 | | | | | |
| | Basic dynamic load rating C N | | Basic static load rating C_0 N | Allowable rotational speed (2) rpm | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952379111 |
| Diam. intérieur | 35 mm |
| Diam. extérieur | 47 mm |
| Épaisseur | 30 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE