

Roulement à aiguilles RNA49-42-U-IKO - RNA49-42-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/rna49-42-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_a (1)
50	—	RNA 49/42U	—	—	173	50	65	22	0.6
Standard rounding dimension D_s Max. mm									
	Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed(2) rpm						
61	38 000	60 900	4 000						

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952379272
Diam. intérieur	50 mm
Diam. extérieur	65 mm
Épaisseur	22 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE