


Roulement à aiguilles RNA49-48-UU-IKO - RNA49-48-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/rna49-48-uu-iko>

I KO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
55	RNA 49/48UU	—	—	—	187	55	70	22	0.6
Standard mounting diameter D_A Max. mm	Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed (2) rpm						
66	39 600	66 100	3 500						

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	I KO
N° Ean13	3663952379333
Diam. intérieur	55 mm
Diam. intérieur	2.165" inch
Diam. extérieur	70 mm
Diam. extérieur	2.756" inch
Epaisseur	22 mm
Epaisseur	0.866" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE